

Technical Data Sheet

Excelsior Engineered Oak

The EXCELSIOR Oak range is crafted with a Hardwood Plywood core material and a European Oak 4mm top layer. Lightly brushed with a Matt finish available in twelve different colours.

Specifications

- Species: European Oak
- Core Material: Hardwood Plywood
- Grade: Mixed Grade
- Surface: Brushed
- Coating: UV Lacquer (9)
- Gloss Level: Matt - 10%
- Profile: Tongue & Groove
- Edge Profile: Micro Bevel
- Wear Layer: 4mm (nominal)
- Width: 220mm
- Thickness: 15mm
- Length: 2200mm* 75% Full / 25% Short
- Glue: E1 glue
- Pack Size: 2.42m² box
- Installation: Direct Stick
- Sub-floors: Concrete / Plywood
- Hardness : 5.5 (kN) Janka

Colours Available

Ashen, Greige, Iceberg, Limewash White, Linen, Loam, Natural, Pebble Grey, Sandstone, Storm, Walnut & Whiskey. Also available in Unfinished RAW & Herringbone



Certifications

- FSC
- Slip Resistance: P3 - AS4586:2013
- Fire Rating: CHF Value - 3.8 kW/m² (mean) AS ISO 9239.1:2003 - Smoke Value - 13 %.min (mean)
- Heated Slabs: Maximum 27C * Conditions apply

Warranty*

- 15 Year Residential / Commercial Structural Integrity*
- *Conditions apply (see Warranty)

